



SSM - SSM/HP

Forestry tiller for tractors between 150 and 300 HP with a max working depth of 40 cm.

Standard equipment: double side gear type transmission, PTO drive shaft with cam clutch, gearbox with freewheel, hydraulic rear hood. In addition, for the **SSM/HP** model: stronger transmission for tractors up to 300 HP.

Options: hydraulic top link, hydraulic support roller for height adjustment, adjustable dosing blade.

Notes: For their correct usage, a creeper gear transmission is recommended.



SSM

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type A+MH
	min	max						
SSM 200	150	250	1000	2040	2410	3090	400	76A+4MH
SSM 225	170	250	1000	2280	2650	3340	400	88A+4MH
SSM 250	190	250	1000	2520	2890	3590	400	102A+4MH

SSM/HP

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type A+MH
	min	max						
SSM/HP 200	150	300	1000	2040	2410	3140	400	76A+4MH
SSM/HP 225	170	300	1000	2280	2650	3390	400	88A+4MH
SSM/HP 250	190	300	1000	2520	2890	3640	400	102A+4MH

The data refers to the machine without options.



Rotor type SSM



Tooth type A



Side scraper Type MH