



UMH - UMH/S

Forestry mulcher with fixed teeth rotor for tractors between 110 and 350 HP.

Standard equipment: PTO drive shaft with cam clutch, gearbox with freewheel, hydraulic rear hood, adjustable skids, hydraulic top link, self ranging system of the PTO drive shaft/gearbox, possibility to have the rotor equipped with tooth type „A“ or tooth type „C“.

Options: hydraulic pushing frame, special skids to go underground, rake teeth on hydraulic hood, pushing frame.

Notes: For their correct usage, creeper gear transmission and reversible driving console are recommended.



UMH

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight with		Grinding diameter mm (max)	Teeth q.ty	
	min	max				type C Kg	type A Kg		type A	type C
UMH 150	110	150	1000	1450	1980	2730	3050	400	60A+2C/SD	32C+2C/SD
UMH 175	130	150	1000	1690	2220	2910	3230	400	70A+2C/SD	36C+2C/SD
UMH 200	160	280	1000	1930	2550	3340	3690	400	78A+2C/SD	40C+2C/SD
UMH 225	180	280	1000	2170	2790	3520	3870	400	88A+2C/SD	44C+2C/SD
UMH 250	200	280	1000	2410	3030	3700	4050	400	96A+2C/SD	48C+2C/SD

UMH/S

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight with		Grinding diameter mm (max)	Teeth q.ty	
	min	max				type C Kg	type A Kg		type A	type C
UMH/S 200	160	350	1000	1930	2550	3550	3750	400	78A+2C/SD	40C+2C/SD
UMH/S 225	180	350	1000	2170	2790	3760	4010	400	88A+2C/SD	44C+2C/SD
UMH/S 250	200	350	1000	2410	3030	3910	4270	400	96A+2C/SD	48C+2C/SD

The data refers to the machine without options.



Rotor type UMM/S "A"



Tooth type A



Tooth type C/SD



Rotor type UMM/S "C"



Tooth type C



Tooth type C/SD