



UML/EX

Mulcher with fixed teeth rotor for excavators having a weight between 10 and 18 t.

Standard equipment: 56 cc hydraulic piston motor with double relief valve with anticavitation and brake function, hydraulic hood, adjustable skirts, possibility to have the rotor equipped with tooth type “C” or type “Viper”.

Options: custom made attachment plate with pins, 63 cc hydraulic piston motor, diverter valve.



UML/EX

Model	Power HP	Requirements	Excavator weight	Overall	Weight	Grinding	Teeth	Teeth	
	Min - Max	Flow L/min Min - Max							Pressure Bar Min - Max
UML/EX 100	90 - 100	110 - 140	220 - 350	10 - 18	970	875	200	20+2	22
UML/EX 125	90 - 100	110 - 140	220 - 350	10 - 18	1210	920	200	26+2	28
UML/EX 150	100 - 120	110 - 140	220 - 350	10 - 18	1450	965	200	32+2	34
UML/EX 175	100 - 120	110 - 140	230 - 350	10 - 18	1690	1065	200	36+2	38
UML/EX 200	120 - 130	110 - 140	240 - 350	10 - 18	1930	1145	200	42+2	44

The data refers to the machine without options.



Rotor type UML/EX



Tooth type C



Tooth type C/SD



Rotor type Viper



Tooth type Viper