



UML/SSL

Mulcher with fixed teeth rotor for skid steer loaders between 75 and 120 HP, equipped with a high flow kit.

Standard equipment: 63 cc hydraulic piston motor with double relief valve with anticavitation and brake function, hydraulic hood, adjustable skids, working pressure control gauge, hydraulic hoses, pushing frame, possibility to have the rotor equipped with tooth type "C" or type "Viper".

Options: diverter valve, 56 cc hydraulic piston motor, oil cooler kit.



UML/SSL

Model	Power HP	Requirements	Pressure Bar	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth	Teeth
	Min - Max	Flow L/min						Min - Max	q.ty/type
		Min - Max	Min - Max					C+C/SD	Viper
UML/SSL 125	75 - 110	120 - 150	200 - 350	1210	1590	980	200	26+2	28
UML/SSL 150	75 - 110	120 - 150	200 - 350	1450	1830	1074	200	32+2	34
UML/SSL 175	85 - 120	120 - 150	230 - 350	1690	2070	1170	200	36+2	38

The data refers to the machine without options.



Rotor type UML/SSL



Tooth type C



Tooth type C/SD



Rotor type Viper



Tooth type Viper