



UMM/S UMM/S/HP

Forestry mulcher with fixed teeth rotor for tractors between 130 and 280 HP.

Standard equipment: PTO drive shaft with cam clutch, gearbox with freewheel, hydraulic rear hood, adjustable skids, hydraulic top link, self ranging system of the PTO drive shaft/gearbox. UMM/S/HP stronger transmission for tractors up to 280 HP, possibility to have the rotor equipped with tooth type „B“ or tooth type „C“.

Options: hydraulic pushing frame, special skids to go underground, rake teeth on hydraulic hood, pushing frame.

Notes: For their correct usage, creeper gear transmission and reversible driving console are recommended.



UMM/S

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight with		Grinding diameter mm (max)	Teeth q.ty	
	min	max				type C Kg	type B Kg		type B	type C
UMM/S 200	130	220	1000	1930	2490	2660	2970	350	80B+2C/SD	44C+2C/SD
UMM/S 225	140	220	1000	2170	2730	2780	3090	350	88B+2C/SD	50C+2C/SD
UMM/S 250	150	220	1000	2410	2970	2900	3210	350	102B+2C/SD	56C+2C/SD

UMM/S/HP

Model	Tractor HP		PTO rpm	Working width mm	Overall width mm	Weight with		Grinding diameter mm (max)	Teeth q.ty	
	min	max				type C Kg	type B Kg		type B	type C
UMM/S/HP 200	130	280	1000	1930	2490	2710	3200	350	80B+2C/SD	44C+2C/SD
UMM/S/HP 225	140	280	1000	2170	2730	2830	3140	350	88B+2C/SD	50C+2C/SD
UMM/S/HP 250	150	280	1000	2410	2970	2950	3260	350	102B+2C/SD	56C+2C/SD

The data refers to the machine without options.



Rotor type UMM/S "B"



Tooth type B



Tooth type C/SD



Rotor type UMM/S "C"



Tooth type C



Tooth type C/SD