



## UMM

Forestry mulcher with fixed teeth rotor for tractors between 80 and 180 HP.

**Standard equipment:** PTO drive shaft with cam clutch, gearbox with freewheel, hydraulic rear hood, adjustable skids.

**Options:** hydraulic top link, hydraulic pushing frame, special skids to go underground, raker teeth on hydraulic hood (only for 200, 225 and 250), pushing frame.

**Notes:** For their correct usage, creeper gear transmission and reversible driving console are recommended.



## UMM

Model	Tractor HP min	Tractor HP max	PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type C+C/SD	Teeth q.ty/type Viper
UMM/ST 150	80	110	540 o 1000	1450	1930	1360	300	32C+2C/SD	34
UMM/ST 175	90	110	540 o 1000	1690	2170	1450	300	38C+2C/SD	40
UMM/DT 200	100	180	1000	1930	2490	1830	300	42C+2C/SD	44
UMM/DT 225	110	180	1000	2170	2730	1910	300	46C+2C/SD	48
UMM/DT 250	120	180	1000	2410	2970	1990	300	50C+2C/SD	52

The data refers to the machine without options.



Rotor type UMM



Tooth type C



Tooth type C/SD



Rotor type Viper



Tooth type Viper